## NSN 5985-00-549-9630

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-549-9630

Application Design:
Waveguide
Body Style:
Waveguide type
Overall Length:
2.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.280 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.220 inches
Overall Height:
1.625 inches
Overall Width:
Between 2.750 inches and 3.000 inches
Unthreaded Mounting Hole Diameter:
Between 0.144 inches and 0.147 inches
Operating Tempurature Range:
+0.0/+71.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Mounting Facility Screw Thread Series Designator:
Unc
0110
Waveguide Flange Type:
Waveguide Flange Type:
Waveguide Flange Type: Choke
Waveguide Flange Type: Choke Waveguide Flange Designation:
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u Overall Attenuation Range In Decibels:
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u Overall Attenuation Range In Decibels: +0.2/+10.0
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u Overall Attenuation Range In Decibels: +0.2/+10.0 Attenuation Variation Method:
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u Overall Attenuation Range In Decibels: +0.2/+10.0 Attenuation Variation Method: Continuous
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u Overall Attenuation Range In Decibels: +0.2/+10.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity:
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u Overall Attenuation Range In Decibels: +0.2/+10.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 terminal w/mounting holes
Waveguide Flange Type: Choke  Waveguide Flange Designation: Ug-136b/u  Overall Attenuation Range In Decibels: +0.2/+10.0  Attenuation Variation Method: Continuous  Mounting Facility Type And Quantity: 4 terminal w/mounting holes  Frequency Range:
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u Overall Attenuation Range In Decibels: +0.2/+10.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 terminal w/mounting holes Frequency Range: Between 8.200 gigahertz and 12.400 gigahertz
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u Overall Attenuation Range In Decibels: +0.2/+10.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 terminal w/mounting holes Frequency Range: Between 8.200 gigahertz and 12.400 gigahertz Mounting Thread Quantity:
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u Overall Attenuation Range In Decibels: +0.2/+10.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 terminal w/mounting holes Frequency Range: Between 8.200 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u Overall Attenuation Range In Decibels: +0.2/+10.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 terminal w/mounting holes Frequency Range: Between 8.200 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:
Waveguide Flange Type: Choke Waveguide Flange Designation: Ug-136b/u Overall Attenuation Range In Decibels: +0.2/+10.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 terminal w/mounting holes Frequency Range: Between 8.200 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 knob

0.164 inches

## NSN 5985-00-549-9630

Variable Attenuator - Page 2 of 2



Terminal Type A	nd Quantity:
-----------------	--------------

2 flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0