

View Online at <https://aerobasegroup.com/nsn/5985-00-551-3238>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Inside Diameter:

1.000 inches all flanges and 1.060 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.166 inches all flanges single connection facility and 0.172 inches all flanges single connection facility

Voltage Standing Wave Ratio:

1.07

Insertion Loss In Decibels:

0.05

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges single connection facility

Flange Style:

Choke type all flanges

Waveguide Leg Length:

0.844 inches

Waveguide Longer Leg Length:

3.532 inches

Waveguide Center To Center Distance:

3.312 inches

Waveguide Height:

5.688 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment

Surface Treatment:

Oxide film single tubing segment inside surfaces

Style Designator:

U-bend type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0