

View Online at <https://aerobasegroup.com/nsn/5985-00-552-9040>

Body Style:

Irregular

Overall Length:

3.438 inches

Overall Height:

3.125 inches

Overall Width:

3.125 inches

Frequency Rating:

0.0 gigahertz and 10.8 gigahertz single frequency operating
0.0 gigahertz and 10.8 gigahertz single frequency rf power handling
0.0 gigahertz and 10.8 gigahertz single frequency voltage standing wave ratio
0.0 gigahertz and 10.8 gigahertz single frequency insertion loss
reference
0.0 gigahertz and 10.8 gigahertz single frequency crosstalk reference

Unthreaded Mounting Hole Diameter:

0.218 inches

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

2.500 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

2.500 inches single mounting facility pattern

Operating Temperature Range:

-67.0/+165.0 degrees fahrenheit

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.50 single

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Rf Power Handling Capability:

100.0 watts peak single

Minimum Crosstalk Rating In Decibels:

55.0 single

Actuator Operating Method:

Manual

Switch Operation Sequence:

Makes before breaks

Pole Quantity:

1

Throw Quantity:

2

Rf Maximum Voltage Rating:

500.0 volts rms

Coupling Position Quantity:

2

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Copper alloy body

Precious Material And Location:

Body silver

Precious Material:

Silver

Surface Treatment:

Silver body outside surfaces

Terminal Type And Quantity:

3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0