NSN 5985-00-553-6532

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-553-6532

Cross Sectional Shape: Internal, rectangular external, rectangular **Thread Class:** 2a first flange all connection facilities Thread Direction: Right-hand first flange all connection facilities **Bend Angle In Deg:** 90.0 single bend e-plane **Tubing Wall Construction Style:** Seamless single tubing segment Flange Quantity: 2 Flange Inside Width: 1.003 inches second flange Flange Inside Height: 0.505 inches second flange Flange Outside Width: 1.625 inches second flange Flange Outside Height: 1.625 inches first flange Flange Depth: 0.438 inches second flange Flange Connecting Hole Diameter: 0.169 inches second flange all connection facilities **Voltage Standing Wave Ratio:** 1.05 **Insertion Loss In Decibels:** 0.03 Waveguide Outside Width: Between 0.996 inches and 1.004 inches **Thread Size:** 0.164 inches first flange all connection facilities Waveguide Inside Width: Between 0.896 inches and 0.904 inches Waveguide Inside Height: Between 0.396 inches and 0.404 inches Waveguide Outside Height: Between 0.496 inches and 0.504 inches Waveguide Longer Offset Distance: 3.562 inches Flange Connecting Facility And Quantity: 4 unthreaded hole second flange single connection facility

NSN 5985-00-553-6532

Waveguide Assembly - Page 2 of 2



Flange Style: Cover type second flange Waveguide Offset Distance: 3.562 inches Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Enamel single tubing segment outside surfaces Style Designator: Bend type **Thread Series Designator:** Unc first flange all connection facilities Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: A073a0