NSN 5985-00-555-8725

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-555-8725

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 all bends e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches second flange and 1.006 inches second flange

Flange Inside Height:

0.503 inches second flange and 0.506 inches second flange

Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Inside Diameter:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.422 inches second flange and 0.453 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility and 0.172 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

NSN 5985-00-555-8725

Waveguide Assembly - Page 2 of 2



Flange Connecting Facility And Quantity: 4 unthreaded hole second flange single connection facility Flange Style: Cover type second flange **Waveguide Center To Center Distance:** 1.875 inches **Waveguide Height:** 1.975 inches **Special Features:** Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange **Surface Treatment:** Oxide film all tubing segment and flange outside surfaces **Style Designator:** Double bend type **Thread Series Designator:** Unc first flange single connection facility Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

Fiig: A073a0