NSN 5985-00-556-1247

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-556-1247

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.705 inches second flange and 0.707 inches second flange

Flange Inside Height:

0.394 inches second flange and 0.396 inches second flange

Flange Outside Width:

1.298 inches second flange and 1.328 inches second flange

Flange Outside Height:

1.298 inches second flange and 1.328 inches second flange

Flange Inside Diameter:

0.985 inches first flange and 1.015 inches first flange

Flange Depth:

0.360 inches first flange and 0.390 inches first flange

Flange Connecting Hole Diameter:

0.144 inches second flange all connection facilities and 0.147 inches second flange all connection facilities

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.619 inches and 0.624 inches

Waveguide Inside Height:

Between 0.308 inches and 0.313 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

NSN 5985-00-556-1247 Waveguide Assembly - Page 2 of 2



Waveguide Length:
3.000 inches
Waveguide Center To Center Distance:
0.750 inches
Flexibility:
Rigid single tubing segment
Material:
Copper alloy all tubing segment and flange
Precious Material And Location:
nterior flange surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver all tubing segment and flange inside surfaces
Style Designator:
Offset bend type
Thread Series Designator:
Unc first flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Fiig:
4073a0