

View Online at <https://aerobasegroup.com/nsn/5985-00-556-6010>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange single connection facility

Thread Direction:

Right-hand second flange single connection facility

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches first flange and 1.006 inches first flange

Flange Inside Height:

0.503 inches first flange and 0.506 inches first flange

Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.423 inches second flange and 0.453 inches second flange

Flange Connecting Hole Diameter:

0.169 inches first flange single connection facility

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches second flange single connection facility

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Waveguide Longer Offset Distance:

2.412 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

Flange Style:

Cover type first flange

Waveguide Offset Distance:

1.250 inches

Special Features:

Tubing wall construction can also be laminated

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment

Surface Treatment:

Oxide film all tubing segment and flange outside surfaces

Style Designator:

Bend type

Thread Series Designator:

Unc second flange single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0