

View Online at <https://aerobasegroup.com/nsn/5985-00-557-5208>

Body Style:

Rectangular

Overall Length:

4.200 inches

Overall Height:

2.380 inches

Overall Width:

0.850 inches

Frequency Rating:

0.0 gigahertz and 11.0 gigahertz single frequency operating
0.0 gigahertz and 11.0 gigahertz single frequency rf power handling
0.0 gigahertz and 11.0 gigahertz single frequency voltage standing wave ratio
0.0 gigahertz and 11.0 gigahertz single frequency insertion loss
reference
0.0 gigahertz and 11.0 gigahertz single frequency crosstalk reference

Unthreaded Mounting Hole Diameter:

0.140 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

1.096 inches single mounting facility pattern

Operating Temperature Range:

-65.0/+185.0 degrees fahrenheit

Voltage Standing Wave Ratio:

1.40 single

Insertion Loss In Decibels:

0.35 single

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Rf Power Handling Capability:

300.0 watts average single

Minimum Crosstalk Rating In Decibels:

15.0 single

Actuator Operating Method:

Relay

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Makes before breaks

Switching Time:

20.0 milliseconds

Pole Quantity:

1

Throw Quantity:

2

Rf Maximum Voltage Rating:

500.0 volts rms

Coupling Position Quantity:

2

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Aluminum body

Surface Treatment:

Nickel body outside surfaces

Terminal Type And Quantity:

3 receptacle, coaxial and 4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A158a0