

View Online at <https://aerobasegroup.com/nsn/5985-00-557-6117>

Thread Class:

2b mounting facility stud

Body Style:

Rectangular

Overall Length:

2.625 inches

Overall Height:

2.000 inches

Overall Width:

2.500 inches

Frequency Rating:

0.0 gigahertz and 3.0 gigahertz single frequency voltage standing wave ratio

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

0.938 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.875 inches single mounting facility pattern

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.20 single

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Rf Power Handling Capability:

500.0 watts average single

Minimum Crosstalk Rating In Decibels:

70.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

1.0 ac

Actuator Voltage In Volts:

115.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

15.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Thread Size:

0.112 inches mounting facility stud

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Steel body

Thread Series Designator:

Unc mounting facility stud

Terminal Type And Quantity:

2 tab, solder lug and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A158a0