NSN 5985-00-557-9207

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-557-9207

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 first bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange and 1.256 inches second flange

Flange Inside Height:

0.628 inches second flange and 0.631 inches second flange

Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

Flange Inside Diameter:

1.253 inches first flange and 1.360 inches first flange

Flange Depth:

0.922 inches second flange and 0.953 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility and 0.172 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.05

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

NSN 5985-00-557-9207

Waveguide Assembly - Page 2 of 2



Flange Connecting Facility And Quantity: 4 unthreaded hole second flange single connection facility Flange Style: Cover type second flange **Waveguide Center To Center Distance:** 4.250 inches **Waveguide Height:** 8.500 inches **Special Features:** Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment **Surface Treatment:** Oxide film all tubing segment and flange outside surfaces **Style Designator:** Double bend type **Thread Series Designator:** Unc first flange single connection facility Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A073a0