

View Online at <https://aerobasegroup.com/nsn/5985-00-557-9211>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b all flanges single connection facility

**Thread Direction:**

Right-hand all flanges single connection facility

**Bend Angle In Deg:**

90.0 all bends e-plane

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.897 inches all flanges and 0.903 inches all flanges

**Flange Inside Height:**

0.397 inches all flanges and 0.403 inches all flanges

**Flange Outside Width:**

1.610 inches all flanges and 1.640 inches all flanges

**Flange Outside Height:**

1.610 inches all flanges and 1.640 inches all flanges

**Flange Inside Diameter:**

1.000 inches all flanges and 1.060 inches all flanges

**Flange Depth:**

0.423 inches all flanges and 0.453 inches all flanges

**Voltage Standing Wave Ratio:**

1.08

**Insertion Loss In Decibels:**

0.10

**Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

**Thread Size:**

0.164 inches all flanges single connection facility

**Waveguide Inside Width:**

Between 0.896 inches and 0.904 inches

**Waveguide Inside Height:**

Between 0.396 inches and 0.404 inches

**Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

**Flange Connecting Facility And Quantity:**

4 threaded hole all flanges single connection facility

**Flange Style:**

Choke type all flanges

**Waveguide Center To Center Distance:**

Between 5.797 inches and 5.827 inches

**Waveguide Height:**

4.062 inches

**Special Features:**

Tubing wall construction can also be laminated

**Flexibility:**

Rigid single tubing segment

**Material:**

Aluminum alloy single tubing segment

**Surface Treatment:**

Oxide film all tubing segment and flange outside surfaces

**Style Designator:**

Double bend type

**Thread Series Designator:**

Unc all flanges single connection facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0