# NSN 5985-00-559-3969

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-559-3969

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### Bend Angle In Deg:

90.0 single bend e-plane

#### **Tubing Wall Construction Style:**

Seamless single tubing segment

#### Flange Quantity:

2

#### Flange Inside Width:

1.003 inches second flange and 1.006 inches second flange

#### Flange Inside Height:

0.504 inches second flange and 0.506 inches second flange

#### Flange Outside Width:

2.500 inches first flange

#### Flange Outside Height:

1.750 inches first flange

#### Flange Depth:

0.656 inches first flange

## Flange Connecting Hole Diameter:

0.169 inches all flanges single connection facility and 0.172 inches all flanges single connection facility

# **Voltage Standing Wave Ratio:**

1.07

#### **Insertion Loss In Decibels:**

0.03

### **Maximum Operating Pressure:**

10.0 pounds per square inch gage

# **Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

#### **Waveguide Inside Width:**

Between 0.896 inches and 0.904 inches

#### **Waveguide Inside Height:**

Between 0.396 inches and 0.404 inches

#### **Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

# **Waveguide Longer Offset Distance:**

1.500 inches

#### Flange Connecting Facility And Quantity:

8 unthreaded hole first flange single connection facility

#### Flange Style:

Contact type second flange

#### **Waveguide Offset Distance:**

4.188 inches

# NSN 5985-00-559-3969

Waveguide Assembly - Page 2 of 2



Flexibility:
Rigid single tubing segment
Material:
Copper alloy single tubing segment
Surface Treatment:
Oxide film all tubing segment and flange outside surfaces
Style Designator:
Bend type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

**Fiig:** A073a0