NSN 5985-00-563-1568

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-563-1568

	-		_	_	
	Ina	hla	TA	Deco	MO:
•	JIIA	DIC		DECL	JUE.

Internal, rectangular external, rectangular

End Application:

Radar set an/tps-43e

Tubing Wall Construction Style:

Straight seam single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.840 inches all flanges

Flange Inside Height:

1.340 inches all flanges

Flange Outside Width:

4.250 inches all flanges

Flange Outside Height:

2.750 inches all flanges

Flange Depth:

0.360 inches all flanges

Flange Connecting Hole Diameter:

0.216 inches all flanges first connection facility and 0.222 inches all flanges first connection facility

Voltage Standing Wave Ratio:

1.08

Insertion Loss In Decibels:

0.06

Maximum Operating Pressure:

35.0 pounds per square inch gage

Waveguide Outside Width:

Between 2.994 inches and 3.006 inches

Waveguide Inside Width:

Between 2.834 inches and 2.846 inches

Waveguide Inside Height:

Between 1.334 inches and 1.346 inches

Waveguide Outside Height:

Between 1.494 inches and 1.506 inches

Flange Connecting Facility And Quantity:

6 unthreaded hole all flanges first connection facility

Flange Style:

Contact type all flanges

Waveguide Length:

1.167 feet

Special Features:

Freq range 2.9 to 3.1 ghz

NSN 5985-00-563-1568 Waveguide Assembly - Page 2 of 2



Flexibility:
Flexible single tubing segment
Material:
Rubber natural single tubing jacket
Surface Treatment:
Paint all flange outside surfaces
Style Designator:
Straight type
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A073a0