NSN 5985-00-563-9352

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-563-9352

Application Design:
Waveguide
Body Style:
Waveguide type
Overall Length:
15.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.280 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.220 inches
Overall Height:
7.625 inches
Overall Width:
4.688 inches
Scale Linearity:
Linear
Unthreaded Mounting Hole Diameter:
0.169 inches
Voltage Standing Wave Ratio:
1.15
Power Rating:
10.0 watts average
Waveguide Flange Type:
Cover
Waveguide Flange Designation:
Ug-135/u
Overall Attenuation Range In Decibels:
+0.0/+70.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 terminal w/mounting holes
Frequency Range:
Between 8.200 gigahertz and 12.400 gigahertz
Overall Attenuation Accuracy In Decibels:
-2.00/+2.00
Segment Attenuation Range In Decibels:
+0.00/+50.00
Adjustment Device Type And Quantity:
1 knob

Mounting Facility Pattern: Four position rectangular

NSN 5985-00-563-9352

Variable Attenuator - Page 2 of 2



Terminal Type And Quantity:
2 flange
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0