NSN 5985-00-564-3058

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-564-3058

A collection Boots
Application Design:
Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
3.000 inches
Overall Width:
3.095 inches
Body Diameter:
2.750 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.940 inches
Body Length:
2.060 inches
Schematic Diagram Designator:
"t"
Distance Between Mounting Facility Centers:
1.500 inches
Power Rating:
600.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.0
Overall Attenuation Range In Decibels:
+1.0/+30.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
30
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 kilohertz and 20.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Mounting Thread Quantity:

32 per inch

NSN 5985-00-564-3058

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
600.0 input-output
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A223a0