NSN 5985-00-564-3058

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-564-3058

| Application Decima |
|--|
| Application Design: |
| Audio |
| Body Style: |
| Cylindrical w/side terminals |
| Overall Length: |
| 3.000 inches |
| Overall Width: |
| 3.095 inches |
| Body Diameter: |
| 2.750 inches |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.940 inches |
| Body Length: |
| 2.060 inches |
| Schematic Diagram Designator: |
| "t" |
| Distance Between Mounting Facility Centers: |
| 1.500 inches |
| Power Rating: |
| 600.0 milliwatts average |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Insertion Loss At Minimum Attenuation In Maximum Decibels: |
| 0.0 |
| Overall Attenuation Range In Decibels: |
| +1.0/+30.0 |
| Attenuation Variation Method: |
| Stepped |
| Step Position Quantity: |
| 30 |
| Attenuation Per Step In Decibels: |
| 1.0 |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Frequency Range: |
| Between 0.000 kilohertz and 20.000 kilohertz |
| Overall Attenuation Accuracy In Decibels: |
| -1.00/+1.00 |
| Mounting Thread Quantity: |

32 per inch

NSN 5985-00-564-3058

Variable Attenuator - Page 2 of 2



| Adjustment Device Type And Quantity: |
|--|
| 1 shaft |
| Mounting Facility Pattern: |
| Two position in-line |
| Shaft Type: |
| Round |
| Mounting Facility Screw Thread Diameter: |
| 0.164 inches |
| Impedance Rating In Ohms: |
| 600.0 input-output |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |

A223a0