# NSN 5985-00-565-1229

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-565-1229

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### Bend Angle In Deg:

90.0 third bend e-plane

## **Tubing Wall Construction Style:**

Seamless single tubing segment

## Flange Quantity:

2

#### Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

#### Flange Inside Height:

0.397 inches all flanges and 0.401 inches all flanges

#### Flange Outside Width:

2.070 inches all flanges and 2.110 inches all flanges

#### Flange Outside Height:

1.570 inches all flanges and 1.610 inches all flanges

#### Flange Depth:

0.480 inches all flanges and 0.520 inches all flanges

# Flange Connecting Hole Diameter:

0.167 inches all flanges single connection facility and 0.171 inches all flanges single connection facility

# **Voltage Standing Wave Ratio:**

1.10

## **Insertion Loss In Decibels:**

0.05

# **Maximum Operating Pressure:**

10.0 pounds per square inch gage

## **Waveguide Outside Width:**

1.000 inches

#### **Waveguide Inside Width:**

0.900 inches

# **Waveguide Inside Height:**

0.400 inches

# **Waveguide Outside Height:**

0.500 inches

## Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges single connection facility

# Flange Style:

Contact type all flanges

## **Special Features:**

Tubing wall construction can also be laminated

#### Flexibility:

Rigid single tubing segment

# NSN 5985-00-565-1229

Waveguide Assembly - Page 2 of 2



ΝЛ	2+	er	10	
IVI	aı	œI.	10	I -

Aluminum alloy single tubing segment

**Surface Treatment:** 

Paint all tubing segment and flange outside surfaces

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A073a0