NSN 5985-00-565-1305

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-565-1305

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange single connection facility

Thread Direction:

Right-hand second flange single connection facility

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Inside Diameter:

1.000 inches all flanges and 1.060 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.166 inches first flange single connection facility and 0.172 inches first flange single connection facility

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches second flange single connection facility

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

NSN 5985-00-565-1305

Waveguide Assembly - Page 2 of 2



Waveguide Longer Offset Distance: 3.000 inches Flange Connecting Facility And Quantity: 4 unthreaded hole first flange single connection facility Flange Style: Choke type all flanges Waveguide Offset Distance: 1.344 inches **Special Features:** Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment **Surface Treatment:** Oxide film all tubing segment and flange outside surfaces Style Designator: Corner type **Thread Series Designator:** Unc second flange single connection facility Shelf Life: Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A073a0

N/a
