

View Online at <https://aerobasegroup.com/nsn/5985-00-570-0073>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange single connection facility

**Thread Direction:**

Right-hand first flange single connection facility

**Bend Angle In Deg:**

90.0 third bend h-plane

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.003 inches second flange and 1.006 inches second flange

**Flange Inside Height:**

0.503 inches second flange and 0.506 inches second flange

**Flange Outside Width:**

1.610 inches second flange and 1.640 inches second flange

**Flange Outside Height:**

1.610 inches first flange and 1.640 inches first flange

**Flange Depth:**

0.422 inches second flange and 0.453 inches second flange

**Flange Connecting Hole Diameter:**

0.169 inches second flange single connection facility

**Voltage Standing Wave Ratio:**

1.14

**Insertion Loss In Decibels:**

0.10

**Maximum Operating Pressure:**

20.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

**Thread Size:**

0.164 inches first flange single connection facility

**Waveguide Inside Width:**

Between 0.896 inches and 0.904 inches

**Waveguide Inside Height:**

Between 0.396 inches and 0.404 inches

**Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange single connection facility

**Flange Style:**

Cover type second flange

**Waveguide Length:**

Between 5.775 inches and 5.805 inches

**Waveguide Center To Center Distance:**

Between 3.985 inches and 4.015 inches

**Special Features:**

Mtg. Bracket 2.000 in. Lg., 1.750 in. W. And 0.063 in. Thk., four panel fastener assemblies pressed into bracket on 1.562 in. Porm 0.010 in. By 1.125 in. Porm 0.010 in. Mtg. Centers, bracket located 0.750 in. From center of short leg on e-plane section after second 90 deg. Bend, tubing wall construction can also be laminated

**Flexibility:**

Rigid single tubing segment

**Material:**

Aluminum alloy single tubing segment

**Surface Treatment:**

Oxide film all tubing segment and flange outside surfaces

**Style Designator:**

Offset bend type

**Thread Series Designator:**

Unc first flange single connection facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0