

View Online at <https://aerobasegroup.com/nsn/5985-00-574-6082>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 single bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches first flange and 0.904 inches first flange

Flange Inside Height:

0.396 inches first flange and 0.404 inches first flange

Flange Outside Width:

1.610 inches first flange and 1.640 inches first flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Inside Diameter:

1.407 inches first flange and 1.437 inches first flange

Flange Depth:

0.423 inches first flange and 0.453 inches first flange

Maximum Operating Pressure:

45.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Waveguide Longer Offset Distance:

Between 1.252 inches and 1.272 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

Flange Style:

Choke type first flange

Waveguide Offset Distance:

Between 0.990 inches and 1.010 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum single tubing segment

Surface Treatment:

Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

Style Designator:

Bend type

Thread Series Designator:

Unc first flange all connection facilities

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0