

View Online at <https://aerobasegroup.com/nsn/5985-00-575-0273>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

90.0 all bends h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

Flange Inside Height:

0.396 inches all flanges and 0.404 inches all flanges

Flange Outside Width:

1.625 inches all flanges

Flange Outside Height:

1.625 inches all flanges

Flange Inside Diameter:

1.216 inches all flanges and 1.224 inches all flanges

Flange Depth:

0.438 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges single connection facility

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.03

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges single connection facility

Flange Style:

Choke type all flanges

Waveguide Center To Center Distance:

2.625 inches

Waveguide Height:

1.250 inches

Flexibility:

Rigid single tubing segment

Material:

Copper alloy single tubing segment

Surface Treatment:

Oxide film all tubing segment and flange outside surfaces

Style Designator:

Double bend type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0