

View Online at <https://aerobasegroup.com/nsn/5985-00-575-0329>

Cross Sectional Shape:

Internal, rectangular external, rectangular

End Application:

Ticonderoga class cg (47); virginia class cgn (41); spruance class dd (963); kidd class ddg; gun fire control system, mk 86

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.118 inches all flanges and 1.126 inches all flanges

Flange Inside Height:

0.493 inches all flanges and 0.501 inches all flanges

Flange Outside Width:

1.875 inches all flanges

Flange Outside Height:

1.875 inches all flanges

Flange Inside Diameter:

1.248 inches all flanges and 1.256 inches all flanges

Flange Depth:

0.625 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges single connection facility

Voltage Standing Wave Ratio:

1.04

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Criticality Code Justification:

Feat

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges single connection facility

Flange Style:

Choke type all flanges

Waveguide Length:

1.021 feet

Special Features:

Weapon system essential

Flexibility:

Rigid single tubing segment

Material:

Copper alloy single tubing segment

Surface Treatment:

Oxide film all tubing segment and flange outside surfaces

Style Designator:

Straight type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0