NSN 5985-00-583-0056

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-583-0056

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 single bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.622 inches second flange

Flange Inside Height:

0.311 inches second flange

Flange Outside Width:

1.312 inches second flange

Flange Outside Height:

1.312 inches second flange

Flange Inside Diameter:

1.000 inches second flange

Flange Depth:

0.375 inches second flange

Flange Connecting Hole Diameter:

0.147 inches second flange single connection facility

Waveguide Outside Width:

0.702 inches

Thread Size:

0.138 inches first flange single connection facility

Waveguide Inside Width:

0.622 inches

Waveguide Inside Height:

0.311 inches

Waveguide Outside Height:

0.391 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Choke type first flange

Waveguide Leg Length:

0.649 inches

NSN 5985-00-583-0056 Waveguide Assembly - Page 2 of 2



| Waveguide Longer Leg Length: |
|---|
| 0.909 inches |
| Waveguide Center To Center Distance: |
| 5.200 inches |
| Flexibility: |
| Rigid single tubing segment |
| Material: |
| Copper alloy all flange |
| Style Designator: |
| U-bend type |
| Thread Series Designator: |
| Unc first flange single connection facility |
| Fsc Application Data: |
| Radar equipment, except airborne |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| |

A073a0