## NSN 5985-00-583-6307

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-583-6307 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Any acceptable **Overall Length:** Between 2.453 inches and 2.547 inches **Overall Diameter:** Between 0.782 inches and 0.842 inches **Voltage Standing Wave Ratio:** 1.20 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Rf Signal Attenuation In Decibels: 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz **Attenuation Accuracy Reference Frequency:** 1.2 gigahertz **Attenuation Accuracy In Decibels:** -1.00/+1.00 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 4.000 gigahertz **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 5985-00-583-6307

Fixed Attenuator - Page 2 of 2



Fiig:

A20000