## NSN 5985-00-586-9875

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-586-9875

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

## **Tubing Wall Construction Style:**

Seamless single tubing segment

Flange Quantity:

2

## Flange Inside Width:

1.003 inches all flanges and 1.006 inches all flanges

## Flange Inside Height:

0.503 inches all flanges and 0.506 inches all flanges

## Flange Outside Width:

1.625 inches all flanges

## Flange Outside Height:

1.625 inches all flanges

## Flange Depth:

0.438 inches all flanges

## Flange Connecting Hole Diameter:

0.169 inches all flanges single connection facility

## **Voltage Standing Wave Ratio:**

1.15

## **Insertion Loss In Decibels:**

0.20

## **Maximum Operating Pressure:**

10.0 pounds per square inch gage

## **Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

## Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

## **Waveguide Inside Height:**

Between 0.396 inches and 0.404 inches

## Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

## Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges single connection facility

## Flange Style:

Contact type all flanges

## Waveguide Length:

8.000 inches

## Flexibility:

Rigid single tubing segment

#### Material:

Copper alloy single tubing segment

# NSN 5985-00-586-9875

Waveguide Assembly - Page 2 of 2



c.	ırfa	'	т.,		4	~ ~	٠.
Ðι	ırıa	ce	11	eа	ш	er	H.

Oxide film all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

**Style Designator:** 

Straight type

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0