

NSN 5985-00-592-0372 Fixed Attenuator - Page 1 of 2	Aero
Tixed Attendator - Fage 1 of 2	
View Online at https://aerobasegroup.com/nsn/5985-00-592-0372	
Application Design:	
Transmission line	
Body Material:	
Metal	
Body Style:	
Round, terminal/terminals in opposite surface	
Body Surface Treatment:	
Silver plated, qq-s-365	
Overall Length:	
2.200 inches	
Overall Diameter:	
0.580 inches	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Voltage Standing Wave Ratio:	
1.20	
Input Impedance Rating In Ohms:	
50.0	
Output Impedance Rating In Ohms:	
50.0	
Coaxial Connector Series Designation:	
Bnc	
Power Rating:	
2.0 watts average and 2.0 kilowatts peak	
Rf Signal Attenuation In Decibels:	
8.0	
Voltage Standing Wave Ratio Frequency Range:	

+0.0/+2.5 gigahertz

Attenuation Accuracy Reference Frequency:

2.5 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 2.500 gigahertz

Precious Material And Location:

Body surfaces silver

NSN 5985-00-592-0372

Fixed Attenuator - Page 2 of 2



Precious Material:	
Silver	
Fsc Application Data:	
Antennas, waveguides, and related equipment	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	

A20000