

View Online at <https://aerobasegroup.com/nsn/5985-00-595-5392>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches second flange and 1.006 inches second flange

Flange Inside Height:

0.503 inches second flange and 0.506 inches second flange

Flange Outside Width:

2.070 inches first flange and 2.110 inches first flange

Flange Outside Height:

1.610 inches second flange and 1.640 inches second flange

Flange Depth:

0.480 inches first flange and 0.520 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility and 0.172 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.02

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

18.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Waveguide Longer Offset Distance:

4.560 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole first flange single connection facility

Flange Style:

Cover type second flange

Waveguide Offset Distance:

1.410 inches

Flexibility:

Rigid first tubing segment

Material:

Beryllium single tubing segment

Surface Treatment:

Paint single tubing segment outside surfaces

Style Designator:

Corner type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0