

View Online at <https://aerobasegroup.com/nsn/5985-00-600-1677>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2a first flange all connection facilities

Thread Direction:

Right-hand first flange single connection facility

Tubing Wall Construction Style:

Convolute single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.006 inches second flange

Flange Inside Height:

1.006 inches second flange

Flange Outside Diameter:

3.625 inches second flange

Flange Depth:

0.938 inches first flange

Flange Connecting Hole Diameter:

0.199 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.08

Insertion Loss In Decibels:

0.03

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

2.000 inches

Thread Size:

0.190 inches first flange all connection facilities

Waveguide Inside Width:

1.872 inches

Waveguide Inside Height:

0.872 inches

Waveguide Outside Height:

1.000 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

1.000 feet

Flexibility:

Flexible single tubing segment

Material:

Copper alloy all tubing segment and flange

Style Designator:

Straight type

Thread Series Designator:

Unf first flange all connection facilities

Specification Data:

81349-mil-w-287/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A073a0