## NSN 5985-00-607-8884

Fixed Attenuator - Page 1 of 2



5
View Online at https://aerobasegroup.com/nsn/5985-00-607-8884
Application Design:
Transmission line
Body Material:
Metal
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Silver plated, qq-s-365
Overall Length:
2.200 inches
Overall Diameter:
0.840 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 2.0 kilowatts peak
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+2.5 gigahertz
Attenuation Accuracy Reference Frequency:
2.5 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Male input and female output
Mounting Method:

Connector

**Terminal Type And Quantity:** 

2 connector

Frequency Range:

Between 0.000 hertz and 2.500 gigahertz

**Precious Material And Location:** 

Body surfaces silver

## **NSN 5985-00-607-8884** Fixed Attenuator - Page 2 of 2



Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A20000