# NSN 5985-00-608-0007

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-608-0007

# **Cross Sectional Shape:**

Internal, rectangular external, rectangular

# Thread Class:

2b first flange all connection facilities

# **Thread Direction:**

Right-hand first flange all connection facilities

# Bend Angle In Deg:

75.0 single bend h-plane

#### **Tubing Wall Construction Style:**

Seamless single tubing segment

# Flange Quantity:

2

#### Flange Inside Width:

1.253 inches second flange and 1.256 inches second flange

#### Flange Inside Height:

0.628 inches second flange and 0.631 inches second flange

#### Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

#### Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

#### Flange Inside Diameter:

1.610 inches first flange and 1.640 inches first flange

# Flange Depth:

0.610 inches first flange and 0.640 inches first flange

# Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

# Voltage Standing Wave Ratio:

1.10

#### Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

# Thread Size:

0.164 inches first flange all connection facilities

#### Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

#### Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

# Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

# Waveguide Longer Offset Distance:

Between 5.422 inches and 5.453 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

# **NSN 5985-00-608-0007** Waveguide Assembly - Page 2 of 2



Flange Style:	
Cover type second	-
Waveguide Offse	et Distance:
Between 5.422 inc	ches and 5.453 inches
Flexibility:	
Flexible single tub	ing segment
Material:	
Copper alloy first t	tubing segment and flange
Precious Materia	I And Location:
Internal surfaces r	hodium and internal surfaces silver
Precious Materia	l:
Rhodium and silve	Ðr
Surface Treatme	nt:
Rhodium all tubing	g segment and flange inside surfaces and silver all tubing segment and flange inside surfaces
Style Designator	:
Bend type	
Thread Series De	esignator:
Unc first flange all	connection facilities
Fsc Application I	Data:
Antennas, wavegu	uides, and related equipment
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A073a0	