NSN 5985-00-614-2344

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-614-2344

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches all flanges and 1.006 inches all flanges

Flange Inside Height:

0.503 inches all flanges and 0.506 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Waveguide First Leg Length:

Between 2.220 inches and 2.280 inches

Flange Style:

Cover type all flanges

Waveguide Second Leg Length:

Between 3.910 inches and 3.970 inches

Waveguide Third Leg Length:

Between 9.070 inches and 9.270 inches

Waveguide Fourth Leg Length:

23.340 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all tubing segment and flange

NSN 5985-00-614-2344

Waveguide Assembly - Page 2 of 2



Surface Treatment:

Any acceptable all tubing segment and flange outside surfaces

Style Designator:

Three bend type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0