# NSN 5985-00-624-4983

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-624-4983

# Application Design:

Transmission line

## **Body Style:**

Coaxial type

## **Overall Length:**

3.950 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

### 1.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

#### 1.500 inches

### **Overall Height:**

3.000 inches

## Overall Width:

3.000 inches

### Shaft Diameter:

0.250 inches

## \_\_\_\_\_

Shaft Length:

# 0.590 inches

**Operating Tempurature Range:** 

-29.0/+22.0 degrees celsius

## Voltage Standing Wave Ratio:

1.50

**Coaxial Connector Series Designation:** 

Ν

## **Power Rating:**

10.0 watts average and 5.0 kilowatts peak

## Mounting Facility Screw Thread Series Designator:

Unc

# **Overall Attenuation Range In Decibels:**

+0.0/+10.0

# Attenuation Variation Method:

Continuous

# Mounting Facility Type And Quantity:

4 threaded hole

# Frequency Range:

Between 10.000 hertz and 55.000 hertz

# Mounting Thread Quantity:

32 per inch

# Adjustment Device Type And Quantity:

1 shaft

# Mounting Facility Pattern:

Four position rectangular

# NSN 5985-00-624-4983

Variable Attenuator - Page 2 of 2

AeroBase Group

Shaft Type:

Round, slotted

Mounting Facility Screw Thread Diameter:

0.138 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A223a0