## NSN 5985-00-626-4426

Waveguide Assembly - Page 1 of 2



-4426

View Online at https://aerobasegroup.com/nsn/5985-00-626
Cross Sectional Shape:
Internal, rectangular external, rectangular
Tubing Wall Construction Style:
Seamless single tubing segment
Flange Quantity:
2
Voltage Standing Wave Ratio:
1.05
Insertion Loss In Decibels:
0.05
Maximum Operating Pressure:
30.0 pounds per square inch gage
Waveguide Outside Width:
Between 0.996 inches and 1.004 inches
Waveguide Inside Width:
Between 0.896 inches and 0.904 inches
Waveguide Inside Height:
Between 0.396 inches and 0.404 inches
Waveguide Outside Height:
Between 0.496 inches and 0.504 inches
Waveguide Longer Offset Distance:
5.812 inches
Flange Style:
Cover type second flange
Waveguide Offset Distance:
5.812 inches
Flexibility:
Rigid single tubing segment
Material:
Aluminum alloy all tubing segment and flange
Surface Treatment:
Chromate all tubing segment and flange outside surfaces
Style Designator:
Bend type
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:

Demilitarization:

Unit Of Measure:

Yes - demil/mli

N/a

## **NSN 5985-00-626-4426** Waveguide Assembly - Page 2 of 2



Fiig:

A073a0