

View Online at <https://aerobasegroup.com/nsn/5985-00-630-6641>

Thread Class:

2b mounting facility hole

Body Style:

Irregular

Overall Length:

2.200 inches

Overall Height:

2.750 inches

Overall Width:

0.900 inches

Frequency Rating:

150.0 megahertz and 400.0 megahertz single frequency rf power handling 150.0 megahertz and 400.0 megahertz single frequency voltage standing wave ratio 150.0 megahertz and 400.0 megahertz single frequency insertion loss reference

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

0.900 inches single mounting facility pattern

Operating Temperature Range:

-28.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

0.15 single

Coaxial Connector Series Designation:

Tnc

Connector End Design:

Female

Rf Power Handling Capability:

500.0 watts peak single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.25 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

25.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

24 mounting facility hole

Thread Size:

0.190 inches mounting facility hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Special Features:

Has contacts for indicator circuit

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

5 turret and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0