

View Online at <https://aerobasegroup.com/nsn/5985-00-630-6641>

Thread Class:

2b mounting facility hole

Body Style:

Irregular

Overall Length:

2.200 inches

Overall Height:

2.750 inches

Overall Width:

0.900 inches

Frequency Rating:

150.0 megahertz and 400.0 megahertz single frequency rf power handling150.0 megahertz and 400.0 megahertz single frequency voltage standing wave ratio150.0 megahertz and 400.0 megahertz single frequency insertion loss reference

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

0.900 inches single mounting facility pattern

Operating Temperature Range:

-28.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

0.15 single

Coaxial Connector Series Designation:

Tnc

Connector End Design:

Female

Rf Power Handling Capability:

500.0 watts peak single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.25 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

25.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

24 mounting facility hole

Thread Size:

0.190 inches mounting facility hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Special Features:

Has contacts for indicator circuit

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

5 turret and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0