## NSN 5985-00-630-8054

Variable Attenuator - Page 1 of 2

**Application Design:** 

Audio



View Online at https://aerobasegroup.com/nsn/5985-00-630-8054

Body Style:
Cylindrical w/side terminals
Overall Length:
4.266 inches
Overall Width:
1.453 inches
Body Diameter:
1.156 inches
Shaft Diameter:
0.188 inches
Bushing Length:
0.375 inches
Shaft Length:
3.000 inches
Body Length:
1.266 inches
Schematic Diagram Designator:
Bridged "t"
Operating Tempurature Range:
-55.0/+120.0 degrees celsius
Power Rating:
5.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unef
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+49.0
•
+0.0/+49.0
+0.0/+49.0 Attenuation Variation Method:
+0.0/+49.0  Attenuation Variation Method:  Continuous
+0.0/+49.0  Attenuation Variation Method:  Continuous  Mounting Facility Type And Quantity:
+0.0/+49.0  Attenuation Variation Method:  Continuous  Mounting Facility Type And Quantity:  1 threaded bushing
+0.0/+49.0  Attenuation Variation Method:  Continuous  Mounting Facility Type And Quantity:  1 threaded bushing  Overall Attenuation Accuracy In Decibels:
+0.0/+49.0  Attenuation Variation Method:  Continuous  Mounting Facility Type And Quantity:  1 threaded bushing  Overall Attenuation Accuracy In Decibels: -2.00/+2.00
+0.0/+49.0  Attenuation Variation Method: Continuous  Mounting Facility Type And Quantity: 1 threaded bushing  Overall Attenuation Accuracy In Decibels: -2.00/+2.00  Mounting Thread Quantity:
+0.0/+49.0  Attenuation Variation Method: Continuous  Mounting Facility Type And Quantity: 1 threaded bushing  Overall Attenuation Accuracy In Decibels: -2.00/+2.00  Mounting Thread Quantity: 32 per inch
+0.0/+49.0  Attenuation Variation Method:  Continuous  Mounting Facility Type And Quantity:  1 threaded bushing  Overall Attenuation Accuracy In Decibels: -2.00/+2.00  Mounting Thread Quantity:  32 per inch  Adjustment Device Type And Quantity:
+0.0/+49.0  Attenuation Variation Method: Continuous  Mounting Facility Type And Quantity: 1 threaded bushing  Overall Attenuation Accuracy In Decibels: -2.00/+2.00  Mounting Thread Quantity: 32 per inch  Adjustment Device Type And Quantity: 1 shaft
+0.0/+49.0  Attenuation Variation Method: Continuous  Mounting Facility Type And Quantity: 1 threaded bushing  Overall Attenuation Accuracy In Decibels: -2.00/+2.00  Mounting Thread Quantity: 32 per inch  Adjustment Device Type And Quantity: 1 shaft  Shaft Type:

## NSN 5985-00-630-8054

Variable Attenuator - Page 2 of 2



Terminal Type A	nd Quantity:
-----------------	--------------

6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0