

View Online at <https://aerobasegroup.com/nsn/5985-00-632-1273>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

1

Flange Inside Width:

0.896 inches single flange and 0.904 inches single flange

Flange Inside Height:

0.396 inches single flange and 0.404 inches single flange

Flange Outside Width:

1.610 inches single flange and 1.640 inches single flange

Flange Outside Height:

1.610 inches single flange and 1.640 inches single flange

Flange Inside Diameter:

1.406 inches single flange and 1.437 inches single flange

Flange Depth:

0.423 inches single flange and 0.453 inches single flange

Flange Connecting Hole Diameter:

0.169 inches single flange all connection facilities

Voltage Standing Wave Ratio:

1.25

Connector End Design:

Female

Adapter Length:

1.270 inches

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole single flange all connection facilities

Flange Style:

Choke type single flange

Adapterheight:

Between 1.623 inches and 1.627 inches

Adapterwidth:

Between 1.623 inches and 1.627 inches

Special Features:

Frequency range 8.5 ghz to 9.6 ghz

Material:

Aluminum alloy single tubing segment and flange

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Surface Treatment:

Paint single tubing segment and flange outside surfaces

Style Designator:

Waveguide to coaxial

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0