NSN 5985-00-636-8405

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-636-8405

Application Design:	
Waveguide Body Material	
Body Material:	
Brass	
Body Style:	
Waveguide type	
Overall Length:	
7.250 inches	Leventha
Center To Center Distance Between Mounting Facilities Parallel To	Length:
1.000 inches	
Center To Center Distance Between Mounting Facilities Parallel To	Width:
0.938 inches	
Overall Height:	
2.875 inches	
Overall Width:	
2.188 inches	
Unthreaded Mounting Hole Diameter:	
0.156 inches	
Voltage Standing Wave Ratio:	
1.15	
Power Rating:	
500.0 milliwatts average	
Overall Attenuation Range In Decibels:	
+0.0/+20.0	
Attenuation Variation Method:	
Continuous	
Mounting Facility Type And Quantity:	
8 unthreaded hole	
Frequency Range:	
Between 12.400 gigahertz and 18.000 gigahertz	
Adjustment Device Type And Quantity:	
1 knob	
Mounting Facility Pattern:	
Four position rectangular	
Terminal Type And Quantity:	
2 flange	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	

NSN 5985-00-636-8405 Variable Attenuator - Page 2 of 2

Fiig: A223a0

