NSN 5985-00-642-5834

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-642-5834

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.875 inches
Overall Height:
4.122 inches
Overall Width:
4.188 inches
Power Rating:
0.25 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+12.0
Attenuation Variation Method:
Stepped
Stepped Step Position Quantity:
Step Position Quantity:
Step Position Quantity:
Step Position Quantity: 9 Attenuation Per Step In Decibels:
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity:
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 4 threaded hole
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range:
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 500.000 megahertz and 1.500 gigahertz
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 500.000 megahertz and 1.500 gigahertz Overall Attenuation Accuracy In Decibels:
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 500.000 megahertz and 1.500 gigahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 500.000 megahertz and 1.500 gigahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity:
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 500.000 megahertz and 1.500 gigahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 32 per inch
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 500.000 megahertz and 1.500 gigahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 500.000 megahertz and 1.500 gigahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 slotted screw
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 500.000 megahertz and 1.500 gigahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern:
Step Position Quantity: 9 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 500.000 megahertz and 1.500 gigahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern: Four position rectangular

50.0 input-output

NSN 5985-00-642-5834

Variable Attenuator - Page 2 of 2



Terminal '	Type And	Quantity:
ı errilili ar	I VDE AIIU	Qualitity.

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0