NSN 5985-00-644-4620

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-644-4620

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Tubing Wall Construction Style:

Bellows single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Tubing Twist Angle In Deg:

20.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.125 inches second flange

Flange Inside Height:

0.500 inches first flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Depth:

Any acceptable second flange

Flange Connecting Hole Diameter:

0.170 inches second flange single connection facility

Thready Qty Per Inch (tpi):

32 first flange single connection facility

Waveguide Outside Width:

1.500 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.125 inches

Waveguide Inside Height:

0.500 inches

Waveguide Outside Height:

1.000 inches

Waveguide Longer Offset Distance:

8.062 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

NSN 5985-00-644-4620 Waveguide Assembly - Page 2 of 2



Flange Style:
Cover type second flange
Waveguide Offset Distance:
8.062 inches
Flexibility:
Flexible single tubing segment
Material:
Rubber synthetic all tubing jacket
Surface Treatment:
Chromate zinc all flange outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange single connection facility
Fsc Application Data:
Radar equipment except airborne
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A073a0