NSN 5985-00-655-7589

Fixed Attenuator - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5985-00-655-7589

| Application Design: |
|---|
| Transmission line |
| Body Material: |
| Steel, stainless |
| Body Style: |
| Round, terminal/terminals in opposite surface |
| Body Surface Treatment: |
| Passivated |
| Overall Length: |
| 3.094 inches |
| Overall Diameter: |
| 0.781 inches |
| Operating Tempurature Range: |
| -30.0/+70.0 degrees celsius |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| Ν |
| Power Rating: |
| 1.0 watts average |
| Rf Signal Attenuation In Decibels: |
| 10.0 |
| Attenuation Accuracy Reference Frequency: |
| 3.0 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.20/+0.20 |
| Connection Type Per Function: |
| Female input and male output |
| Unpackaged Unit Weight: |
| 4.000 ounces |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 3.000 gigahertz |
| Fsc Application Data: |
| Antennas, waveguides, and related equipment |
| Shelf Life: |
| N/a |
| |

NSN 5985-00-655-7589

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A20000

