

View Online at <https://aerobasegroup.com/nsn/5985-00-665-3042>

Body Style:

Rectangular

Overall Length:

4.290 inches

Frequency Rating:

0.0 gigahertz and 10.0 gigahertz single frequency crosstalk reference

Overall Diameter:

5.000 inches

Unthreaded Mounting Hole Diameter:

0.189 inches

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

2.500 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

2.500 inches single mounting facility pattern

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.52 single

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Rf Power Handling Capability:

100.0 watts average single

Minimum Crosstalk Rating In Decibels:

25.0 single

Actuator Operating Method:

Manual

Switch Operation Sequence:

Breaks before makes

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Aluminum body

Surface Treatment:

Anodize body outside surfaces

Test Data Document:

81349-mil-s-3928 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0