## NSN 5985-00-666-2743



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-666-2743 **Application Design:** Waveguide **Body Style:** Waveguide type **Overall Length:** 12.812 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.375 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.438 inches **Overall Height:** 2.750 inches **Overall Width:** 2.000 inches **Voltage Standing Wave Ratio:** 1.00 and 2.00 **Power Rating:** 0.5 watts average **Mounting Facility Screw Thread Series Designator:** Unc **Overall Attenuation Range In Decibels:** +0.0/+60.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 threaded stud Frequency Range: Between 960.000 megahertz and 1.215 gigahertz **Overall Attenuation Accuracy In Decibels:** -1.00/+1.00 **Mounting Thread Quantity:** 32 per inch **Mounting Facility Pattern:** Four position rectangular **Mounting Facility Screw Thread Diameter:** 0.164 inches Shelf Life:

N/a
Unit Of Measure:
-Demilitarization:
Yes - demil/mli

## NSN 5985-00-666-2743

Variable Attenuator - Page 2 of 2



Fiig:

A223a0