

View Online at <https://aerobasegroup.com/nsn/5985-00-672-3829>

Cross Sectional Shape:

Internal, rectangular external, rectangular

End Application:

Missile guidance and tracking set an/spg-55

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches second flange and 2.005 inches second flange

Flange Inside Height:

1.002 inches second flange and 1.005 inches second flange

Flange Outside Diameter:

3.610 inches second flange and 3.640 inches second flange

Flange Depth:

0.360 inches second flange and 0.390 inches second flange

Flange Connecting Hole Diameter:

0.199 inches second flange all connection facilities and 0.203 inches second flange all connection facilities

Maximum Operating Pressure:

12.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Waveguide Longer Offset Distance:

Between 24.061 inches and 24.091 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Offset Distance:

4.943 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all tubing segment and flange

Surface Treatment:

Chromate zinc all tubing segment and flange outside surfaces and enamel all tubing segment and flange outside surfaces

Style Designator:

Bend type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0