NSN 5985-00-674-5801

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-674-5801

Application Design:
Transmission line
Body Style:
Cylindrical w/side terminals
Overall Length:
4.094 inches
Overall Width:
2.000 inches
Body Diameter:
2.375 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.406 inches
Shaft Length:
2.406 inches
Body Length:
1.686 inches
Schematic Diagram Designator:
"t"
Power Rating:
500.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unef
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Frequency Range:
Between 0.000 kilohertz and 50.000 kilohertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.375 inches

NSN 5985-00-674-5801

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms:
600.0 input-output
Special Features:
Threaded bushing mtg
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A223a0