NSN 5985-00-677-1532

Variable Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-00-677-1532

Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
4.157 inches
Overall Width:
1.344 inches
Body Diameter:
1.125 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.375 inches
Shaft Length:
2.000 inches
Body Length:
1.782 inches
Schematic Diagram Designator:
"t"
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Power Rating:
2.0 watts average
Mounting Facility Screw Thread Series Designator:
Unef
Overall Attenuation Range In Decibels:
+0.0/+30.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 threaded bushing
Frequency Range:
Between 0.000 kilohertz and 20.000 kilohertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.375 inches

NSN 5985-00-677-1532

Variable Attenuator - Page 2 of 2



	Impedance	Rating	ln	Ohms:
--	-----------	--------	----	-------

600.0 input-output

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0