

View Online at <https://aerobasegroup.com/nsn/5985-00-678-2657>

Frequency Rating:

9000.0 megahertz and 9160.0 megahertz single frequency crosstalk reference

Unthreaded Mounting Hole Diameter:

0.281 inches

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

5.750 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

5.500 inches single mounting facility pattern

Voltage Standing Wave Ratio:

1.15 single

Insertion Loss In Decibels:

0.60 single

Rf Power Handling Capability:

250.0 kilowatts peak single

Minimum Crosstalk Rating In Decibels:

20.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.2 dc

Actuator Voltage In Volts:

300.0

Switching Time:

10.0 milliseconds

Waveguide Flange Type:

Cover

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Flange Connecting Facility And Quantity:

12 unthreaded hole

Material:

Aluminum body

Surface Treatment:

Chromate body outside surfaces

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0