

View Online at <https://aerobasegroup.com/nsn/5985-00-681-3586>

Application Design:

Waveguide

Body Material:

Aluminum

Body Style:

Rectangular, terminal/terminals on opposite surfaces

Body Surface Treatment:

Copper flash

Overall Length:

6.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.220 inches

Overall Height:

1.625 inches

Overall Width:

1.625 inches

Mounting Hole/stud Quantity:

4

Inside Width:

0.500 inches

Unthreaded Mounting Hole Diameter:

0.169 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.280 inches

Inside Height:

1.000 inches

Voltage Standing Wave Ratio:

1.00 and 1.15

Power Rating:

1.0 watts average

Rf Signal Attenuation In Decibels:

30.0

Voltage Standing Wave Ratio Frequency Range:

+8.2/+12.4 gigahertz

Waveguide Flange Type:

Cover

Waveguide Flange Designation:

Ug-39/u

Attenuation Accuracy In Decibels:

-0.30/+0.30

Mounting Method:

Terminal w/mounting holes

Terminal Type And Quantity:

2 flange

Frequency Range:

Between 8.200 gigahertz and 12.400 gigahertz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000