NSN 5985-00-681-3586



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-681-3586 **Application Design:** Waveguide **Body Material:** Aluminum **Body Style:** Rectangular, terminal/terminals on opposite surfaces **Body Surface Treatment:** Copper flash **Overall Length:** 6.500 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.220 inches **Overall Height:** 1.625 inches **Overall Width:** 1.625 inches **Mounting Hole/stud Quantity: Inside Width:** 0.500 inches **Unthreaded Mounting Hole Diameter:** 0.169 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.280 inches **Inside Height:** 1.000 inches **Voltage Standing Wave Ratio:** 1.00 and 1.15 **Power Rating:** 1.0 watts average Rf Signal Attenuation In Decibels: **Voltage Standing Wave Ratio Frequency Range:** +8.2/+12.4 gigahertz **Waveguide Flange Type:** Cover **Waveguide Flange Designation:** Ug-39/u **Attenuation Accuracy In Decibels:**

-0.30/+0.30

Mounting Method:

Terminal w/mounting holes

NSN 5985-00-681-3586

Fixed Attenuator - Page 2 of 2



Terminal Type And Quantity	Type And Quantity	T	erminal	Т
----------------------------	-------------------	---	---------	---

2 flange

Frequency Range:

Between 8.200 gigahertz and 12.400 gigahertz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000