

View Online at <https://aerobasegroup.com/nsn/5985-00-683-2188>

**Application Design:**

Transmission line

**Body Material:**

Steel

**Body Style:**

Coaxial type

**Unthreaded Mounting Hole Diameter:**

0.500 inches

**Distance Between Mounting Facility Centers:**

4.750 inches

**End Application:**

Radar set group an/gpa-27

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

30.0

**Overall Attenuation Range In Decibels:**

+30.0/+76.0

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

5

**Attenuation Per Step In Decibels:**

2.0 and 4.0 and 8.0 and 16.0

**Mounting Facility Type And Quantity:**

2 flange w/mounting hole

**Frequency Range:**

Between 0.000 hertz and 30.000 megahertz

**Adjustment Device Type And Quantity:**

5 toggle

**Mounting Facility Pattern:**

Two position in-line

**Impedance Rating In Ohms:**

50.0 input

**Terminal Type And Quantity:**

2 connector, coaxial, female

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A223a0